










Timeless innovation plus unrivaled colors and finishes.


The evolution Terraçade TN

Beautifully thin and sleek, the Terraçade TN range is the pinnacle of ceramic façades. Available in an impressive range of colors and finishes, Terraçade TN is perfectly suited for the modern era.



Terraçade TN Colors and Finishes





Product information

Sizes:

 $11^{13}/_{16}$ " x $46\frac{3}{4}$ " (300mm x 1188mm)

 $11^{13}/_{16}$ " x $23^{1}/_{8}$ " (300mm x 588mm)



Warranties




Color for Life Warranty



100 Year Product Warranty



20 Year System Warranty



Baguettes

Terraçade baguettes have been designed with flexibility in mind. Whether it's performing a privacy function or providing ventilation and shading against the elements, the baguettes will make a statement for any residential, commercial or industrial building.



Product information

Sizes:

 $39\%{3}''$ L x 2" W x 2" H (1000 L x 50 W x 50 H mm)

Warranties








100 Year Product Warranty



20 Year System Warranty





PRODUCT: TN Smooth COLOR: Gibson PROJECT: Shenyang Youth Activity Centre

12





TN SET OUT TOOL

Used to assist in setting out the Terraçade TN Suspension Rails that hold the TN tiles in place.

TN FITMENT SPONGE

When a Terraçade tile is clipped onto the suspension rails (top and bottom) there is a gap between the secured points at the top and the bottom rail where the tile is not fully supported laterally.

The fitment sponge is installed halfway down the tile on the back, centered between the suspension rails vertically and acts to prevent lateral movement of the tile. Four sponges are used for each Terraçade tile.

TN JOINT ANGLE AND CHANNEL

Is used between Terraçade TN tiles to create a clean joint between tiles. This extrusion also helps secure the Terraçade tiles in place.

DRAINING AIR AND WATER BARRIER MEMBRANE

Usually the first component of the system fixed the wall frame, this membrane resists the ingress of water and meets requirements for air barrier materials, while its vapor-permeability and enhanced contours facilitate drying and drainage.

TN SURROUND

This aluminium extrusion is used at the edges (top and sides) of the Terraçade cladded area—it sits around the outside to be create a neat finish and to hold/connect the Terraçade tile to the building frame.

TN EXTERNAL CORNER

This aluminium extrusion finishes the edges of TN tiles at external corners.

TN INTERNAL CORNER

This aluminium extrusion finishes the edges of TN tiles at internal corners.


TN SUSPENSION RAIL

This galvanized steel rail is fixed to the wall frame in a vertical format and provides the anchor points for the Terraçade tiles to clip on to.



Terraçade TN Installation

Terraçade TN 600 Installation




KEY:

- 1 Jointing strip
- 2 Trims
- 3 Tiles
- 4 Membrane
- 5 Vertical rails

Application Length Module Height Thickness Lbs./sq. ft. Internal + 231% and 463% 11 $^{13}\%$ 9 $^{11}\%$ 5.12 External

Terraçade TN 1200 Installation



KEY:

- 1 Jointing strip
- 2 Trims
- 3 Tiles
- 4 Membrane
- 5 Vertical rails

Terraçade TN Installation Recommendations

SEALERS

Cladding

While Terraçade TN offers a low maintenance solution to building façades, there may be instances where more severe conditions exist, such as high traffic areas prone to graffiti. For added protection a sealer may be used.

Terraçade TN Technical Information

Terraçade TN 600	Terraçade TN 1200
23½" (588mm)	46¾" (1188mm)
11 ¹³ / ₁₆ " (300mm)	11 ¹³ / ₁₆ " (300mm)
%16" (14mm)	⁹ / ₁₆ " (14mm)
.52 (5.6/2.7 m²)	.52 (5.6/2.7 m²)
9 (4.5kg)	18 (9kg)
5.12 lbs./269.1 sq. ft. (25/25kg)	5.12 lbs./269.1 sq. ft. (25/25kg)
464.45 lbs. (1.7kN)	464.45 lbs. (1.7kN)
1,284.06 lbs. (4.7kN)	1,284.06 lbs. (4.7kN)
<0.02%	<0.02%
5.6 x 10-7 per °F	5.6 x 10-7 per °F
Exposure Grade	Exposure Grade
0	0
0	0
0	0
0	0
1	1
PASS – Not deemed combustible	PASS – Not deemed combustible
	23½" (588mm) 11 ¹³ ½" (300mm) ½"6" (14mm) .52 (5.6/2.7 m²) 9 (4.5kg) 5.12 lbs./269.1 sq. ft. (25/25kg) 464.45 lbs. (1.7kN) 1,284.06 lbs. (4.7kN) <0.02% 5.6 x 10-7 per °F Exposure Grade 0 0 0 1

Designed to last.

Versatile in design, easy to install and with low maintenance upkeep, Terraçade completes all the steps for any residential, commercial or industrial project.

HIGH DURABILITY

Performs in any environment from extreme heat to freezing temperatures.

ENERGY EFFICIENT

A sustainable material made from natural and recycled material, it naturally assists with airflow and energy reduction.

FIRE RESISTANT

Made from non-combustible material.

TERMITE RESISTANT

No wood, no termites, no degradation.

LOW MAINTENANCE

Life-long colorfastness with a maintenance-free finish.

SUPERIOR STRENGTH

Manufactured for maximum strength and impact resistance.



High durability



Energy efficient



Fire resistant



Termite resistant



Low maintenance



Superior strength



Not all façade materials are the real deal.

Terraçade stands behind all of its products that are rigorously tried and tested to meet strict standards.

COLORFAST

Terraçade tiles will not fade or change color when used in normal weather conditions.

QUALITY TILES

Terraçade tiles used in the Terraçade Façade system are free from defects in materials for a period of 100 years from the date of delivery.

ENDURING SYSTEM

Terraçade Façade system hanging rails are free from defects in materials and workmanship for a period of 20 years from the date of delivery.



Color for Life Warranty



100 Year Product Warranty



20 Year System Warranty



Discover the possibilities at glengery.com

Front cover:

PRODUCT: TN Smooth COLORS: Off-white and Dark Grey