

Technical Data Sheet

Urbanscape Paver Series
Pittsburgh Plant



Product Name	Swatch	Size	Standard	Durability Class (Class)	Dimensional Variation (Application)	Abrasion Resistance (Type)	Compressive Strength (psi)	24-hr Cold Water Absorption (%)	5-hr Boil Absorption (%)	Abrasion Index
Allegheny Grey Paver		4x8	ASTM C902	SX	PS	Type I	>15,000	<6	<10	<0.11
Brownstone Boulevard Paver		4x8	ASTM C902	SX	PS	Type I	>15,000	<6	<10	<0.11
Iron City Full Range Paver		Modular 4x8	ASTM C902	SX	PS	Type I	>10,000	<8	<10	<0.11
Iron City Red Paver		Modular 4x8	ASTM C902	SX	PS	Type I	>10,000	<8	<10	<0.11
Pittsburgh Pearl Paver		4x8	ASTM C902	SX	PS	Type I	>15,000	<6	<10	<0.11
Riverfront Pewter Paver		4x8	ASTM C902	SX	PS	Type I	>15,000	<6	<10	<0.11

This data represents average results. If specific test results are required, sample should be taken from current production lots. U.S. STANDARD TEST METHODS (ASTM C67) ARE USED AS APPLICABLE, UNLESS OTHERWISE NOTED. ©2024

Size	Width	Height	Length	Weight	Brick per Cube	Brick per Sq Ft
Modular	3-9/16"	2-1/4"	7-5/8"	5.4	525	4.50
4x8	4"	2-1/4"	8"	6.3	470	4.50